


**TTP 50 360 VRT L0570 TOP 840 W**  
**RECESSED CEILING ROSE T31 D90 35W 24V HF B**  
 TUBULAR LUMINAIRES

**90555L0600W0000**  
**972750B**



**Light distribution**



**PRODUCT DESCRIPTION**

**Application Areas:** Public spaces, Industry, Outside  
**Mounting Type:** Suspended  
**Control Gear Included:** Yes  
**Control Gear:** 24V transformer

**TTP 50 360 VRT L0570 TOP 840 W**

**CHARACTERISTICS**

**Luminaire Type:** Straight line luminaire  
**Luminaire Module:** Individual  
**Insulation Class:** III  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]-10, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** End cap

**MATERIALS**

**Body Material:** Polycarbonate tube  
**Finishing:** Epoxy polyester powder coated  
**Colour:** White (W)  
**Glow-wire Resistance (°C):** 960

**OPTICAL SYSTEM**

**Optical System:** TOP - Opal diffuser  
**Light Distribution:** Direct  
**Beam Angle (°):** 124

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 9

**Power Factor (λ):** 1

**Luminaire Luminous Flux (lm):** 1119  
**Luminaire Efficacy (lm/W):** 124  
**Unified Glare Rating (UGR):** <22  
**LED Lifetime - Rated Median Useful Life:** 70.000h @ L80, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 4000  
**Colour Rendering Index (CRI):** >80  
**Chromaticity Tolerance (MacAdam step):** <3  
**This Product Contains a Light Source of Energy Efficiency Class:** D  
**LED Module Forward Voltage Range (VF):** 21,5-26,4  
**Input luminaire current (mA):** 392

**DIMENSIONS**

**L - Length (mm):** 570  
**D - Diameter (mm):** Ø50  
**Net Weight (kg):** 0.382

**RECESSED CEILING ROSE T31 D90 35W 24V HF B**

**CHARACTERISTICS**

**Insulation Class:** II  
**Ingress Protection (IP):** 20  
**Ambient Temperature Range (°C):** ]-5, 25[  
**Warranty (Years):** 5

**MATERIALS**

**Colour:** Black (B)

**TECHNICAL DATA**

**Input Power (W):** 35  
**Input Driver Voltage:** 220-240V-50/60Hz

**TTP 50 360 VRT L0570 TOP 840 W  
RECESSED CEILING ROSE T31 D90 35W 24V HF B**

**90555L0600W0000  
972750B**

TUBULAR LUMINAIRES

---

**Power Supply Dimming:** ON/OFF

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <40

**Inrush Current (A):** 30

**Pulse Duration (µs):** 180

### DIMENSIONS

**H - Height (mm):** 36

**D - Diameter (mm):** 90

**D - Recess Dimensions (mm):** 70

**H - Recess Height (mm):** 36

### NOTES

- To complete the product order current supply cable separately;
- The noise level is 20 dB, lower than the typical ambient sound levels recorded in environments such as libraries and reading rooms.